# **Valve Body Selection**


(for 940 Series Heavy Duty Control Valve)


## BRONZE

Single Seat ● 1/2" - 2"




All dimensions are nominal. Dimensions in [ ] are in millimeters.





#### **Stem In-to-Open (normally closed)**



### **Specifications**

<b>Body Material</b>	Trim Material	Trim Style	Connection	Pressure & Temperature Rating
Bronze	Stainless steel	Equal percentage	Threaded	250 PSI @ 400°F (204°C)

#### **Valve Body Selection**

In-To-Close (Normally Open)			Maximum Close-Off Pressure (psid)						
Valve Body	Size		Actuator		Dimensions			Approximate	
Number	Connection (NPT)	) Nominal Port	Cv	940B	940B w/Positioner	A	В	C	Shipping Wt.
J14	1/2	1/2"	4.9	400	400	4.9 [124]	2.9 [74]	2.9 [74]	10 lbs [4.5 kg]
J19	3/4	3/4"	7.2	400	400	4.9 [124]	2.9 [74]	2.9 [74]	10 lbs [4.5 kg]
J26	1	1"	10.0	291	400	4.9 [124]	2.9 [74]	2.9 [74]	10 lbs [4.5 kg]
J36	11/4	1 <sup>1</sup> /4"	22.2	123	327	5.8 [147]	3.3 [84]	3.5 [89]	16 lbs [7.3 kg]
J47	11/2	11/2"	24	123	327	5.8 [147]	3.3 [84]	3.5 [89]	16 lbs [7.3 kg]
J58	2	2"	40	73	200	6.5 [165]	3.6 [91]	3.8 [97]	25 lbs [11.3 kg]

In-To-Open (Normally Closed)				Maximum Close-Off Pressure (psid)					
Valve Body	Size		Actuator		Dimensions			Approximate	
Number	Connection (NPT	) Nominal Port	$C_{\nu}$	940B	940B w/Positioner	A	В	C	Shipping Wt.
J15	1/2	1/2"	4.9	245	400	4.9 [124]	2.9 [74]	2.9 [74]	10 lbs [4.5 kg]
J22	3/4	3/4"	7.2	245	400	4.9 [124]	2.9 [74]	2.9 [74]	10 lbs [4.5 kg]
J30	1	1"	10.0	140	400	4.9 [124]	2.9 [74]	2.9 [74]	10 lbs [4.5 kg]
J41	11/4	11/4"	22.2	55	259	5.8 [147]	3.3 [84]	3.5 [89]	16 lbs [7.3 kg]
J52	11/2	1 <sup>1</sup> /2"	24	55	259	5.8 [147]	3.3 [84]	3.5 [89]	16 lbs [7.3 kg]
J63	2	2"	40	30	157	6.5 [165]	3.6 [91]	3.8 [97]	25 lbs [11.3 kg]